

ERGOMAT®



DURASTRIPE®

- Supreme V

The perfect solution for long lasting floor striping in almost any environment. After long consideration and trials we have chosen to combine the **best of two worlds**: DuraStripe Lean and Supreme. It is therefore our pleasure to introduce to you the next generation of DuraStripe - The **Supreme V**.

This will be the fifth generation (V) of the original DuraStripe and hopefully one which can fulfill the requirements in the market place for a long time to come. The Supreme V combines the adhesive from the original DuraStripe which is the superior choice under non ideal floor conditions along with the low impact profile of DuraStripe Lean. It also has the added benefit of having tapered edges to eliminate most of the potential tripping & impact hazards.


DuraStripe Supreme V 100ft rolls are available in 7 different colors, 2" - 34" widths.

- Ideal for less than perfect floors
- Simple and easy peel-&-stick installation
- No dry time, cure time, fumes or messy clean up to limit productivity
- Backed by a 2-year warranty



New building / smooth floors	Superior
Porous floors	Excellent
Old, oily, dirty, or epoxy floors	Excellent
Uneven or tiles	Excellent
Available in 5S shapes	Yes
Available / custom colors	7 / Yes
Standard widths in inches	5 - 86.5 cm
Beveled edge	Yes
Roll length	30 meters
Nominal thickness	0.91 mm





ERGOMAT®



DURASTRIPE®

- X-Treme

This new **heavy-duty** DuraStripe is made for critical environments and area where pivoting with forklifts / tow motors can occur. DuraStripe X-Treme has a special coated surface that facilitates easy cleaning. The X-Treme as with the DSV, comes with bevel edges to limit damages from dragging of pulling of pallets.

DuraStripe X-Treme is available in 3 standard widths (2", 3", and 4") and 11 standard colors.

- Ideal for smooth or newer floors but can be used on old floors as well
- Ideal tool for 5S, Six Sigma or Visual Factor
- Simple and easy peel-&-stick installation
- Easy to remove for a quick reconfiguration and hence a great Lean Manufacturing tool
- No dry time, cure time, fumes or messy clean up to limit productivity
- Backed by a 2-year warranty

The most rugged peel & stick striping material you can employ.


Recommended for:

- *Rough flooring conditions*
- *Heavy forklift traffic*
- *Challenging and critical environments*



New building / smooth floors	Superior
Porous floors	Superior
Old, oily, dirty, or epoxy floors	Excellent
Uneven or tiles	Superior
Available in 5S shapes	Yes
Available / custom colors	11 / No
Standard widths in inches	5 / 7.5 / 11 cm
Beveled edge	Yes
Roll length	30 meters
Nominal thickness	0.76 mm





ERGOMAT®

DURA STRIPE®

- Mean Lean

Mean Lean DuraStripe is our most economical and lowest profile marking product. It has a durable, smooth surface layer that cleans easily and resists damage from pivoting tow-motor wheels. Because of its low profile, Mean Lean does not have a beveled edge. It is available in 2", 3" and 4" standard widths and 7 Standard colors. It provides a perfect marking solution for:


- Newer or reconditioned/sealed industrial and commercial floors
- 5S, Six Sigma, Visual Workplace and Lean Manufacturing marking programs
- Working environments with light to moderate forklift and pallet jack traffic

Like all DuraStripe products, Mean Lean requires no downtime, no cure time and no messy clean-up to limit productivity, and is backed by a 2-year warranty.



	LEAN	MEAN LEAN
New building / smooth floors	Excellent	Excellent
Porous floors	Not Recommended	N.R.
Old, oily, dirty, or epoxy floors	N.R.	N.R.
Uneven or tiles	N.R.	N.R.
Available in 5S shapes	Yes	Yes
Available / custom colors	7 / No	7 / No
Standard widths in inches	5 - 86.5 cm	5 / 7.5 / 10 cm
Beveled edge	No	No
Roll length	30 meters	30 meters
Nominal thickness	0.76 mm	0.56 mm





ERGOMAT®

DURASTRIPE®

- Hazard Striping

The first and only 100% smear and scuff resistant "caution" striping!
Ideal for alerting workers where to be cautious in the workplace.
Available in widths ranging from 2" all the way to 36".

Hazard striping is ideal for visually warning workers of hazardous work areas. Electrical panels are required to be free from any materials for easy access in case of emergencies. Hazard striping clearly identifies the area and emphasizes the importance of keeping the area clear at all times.

Ideal for good condition floors

Simple and easy peel-&-stick installation

No dry time, cure time, fumes or messy clean up to limit productivity

Custom Colors available, contact us for more information!

Backed by a 2-year warranty

Available Colors

Black/Yellow

Black/White

Red/White

Green/Yellow*

Green/White*

*Colors not available in Lean.



New building / smooth floors	Superior
Porous floors	Excellent
Old, oily, dirty, or epoxy floors	Excellent
Uneven or tiles	Excellent
Available in 5S shapes	Yes
Available / custom colors	7 / Yes
Standard widths in inches	5 - 86.5 cm
Beveled edge	Yes
Roll length	30 meters
Nominal thickness	0.91 mm



DURASTRIPE.

ERGOMAT®

DEEP FREEZE



DuraStripe Deep Freeze is the most rugged peel & stick striping material you can use, ideal for cold/low temperature environments, freezer interiors or other temperature controlled environments.


Deep Freeze DuraStripe combines a durable, impact resistant skin with an aggressive adhesive to deliver a striping material that conquers harsh and cold storage as well as freezing environments. Its specially designed surface layer is engineered to resist damage caused by pivoting and skidding forklift wheels - two of the most common causes of aisle marking destruction. Its beveled edge assists dragged pallets in sliding over the stripe to avoid slicing or tearing even in cold environments.



Technical Data	
Tensile Stress at Break	26 MPa (3700 psi)
Tensile Stress at Yield	48 MPa (6900 psi)
Elongation at Break	58%
Elongation at Yield	4.3%
Tensile Modulus	1950 Mpa (2.8 X 10 ⁵ psi)
Flexural Strength	64 Mpa (9300 psi)
Flexural Modulus	1880 Mpa (2.7 X 10 ⁵ psi)
Rockwell Hardness, R Scale	108
Izod Impact Strength, Notched	
23°C (73°F)	126 J/m (2.4ft lbf/in.)
-40°C (-40°F)	57 J/m (1.0ft lbf/in.)

Adhesive Technical Data	
Thickness	0.13 ± 0.02
Adhesive to Steel*	40
Shear Adhesive** (23°C, 500g, 100mm ²)	30
Temperature Resistance	-40 to +100
Stripe and Adhesive Thickness (mm)	0.5 ± 0.05

The cure time for Deep Freeze adhesive is directly related to application temperature. The ideal application temperature to achieve that most rapid bond is 40 °F (5 °C). If necessary Deep Freeze can be installed at -20 °F (-29 °C), or even lower temperatures, but installation in environments below freezing will prolong the time necessary to achieve maximum bond.



ERGOMAT®



DURASTRIPE®

- OSHA Industries Color-Code



DuraStripe Safety Blue

Designates caution, pertaining specifically to the use of, starting up, or the movement of equipment under repair. Signs indicating the nature of the caution should have blue backgrounds.

Samples of Uses for Safety Blue:

Boilers, elevators, kilns, ovens & vats, piping for protective materials for preventing or reducing hazard of dangerous materials (other than fire fighting)

DuraStripe Safety Black & White

Designates housekeeping and traffic areas.

Examples of Uses for Safety Black & White:

Boundaries of traffic aisles, clear floor space around emergency areas of equipment, directional signs, stairways and dead ends of passageways



DuraStripe Safety Blue



DuraStripe Safety Black & White





ERGOMAT®



DURASTRIPE®

- OSHA Industries Color-Code



DuraStripe Safety Red

Identifies fire protection equipment. Also signifies "danger" and "stop."

Samples of Uses for Safety Red:

extinguishers, fire alarms, blanket boxes, emergency stop bars, containers with flammable liquids, piping that is used for fire fighting, fire protection and sprinkler systems.



DuraStripe Safety Red

DuraStripe Safety Orange

Indicates dangerous parts of machinery or electrical apparatus which can crush, cut or shock.

Samples of Uses for Safety Orange:

Within guards, exposed edges on parts, safety starting buttons and within transmissions guards.



DuraStripe Safety Orange





ERGOMAT®

DURASTRIPE®

- OSHA Industries Color-Code



DuraStripe Safety Yellow

Indicates physical hazards created by non-moving objects which can be fallen over or into, struck against or caught in-between.

Samples of Uses for Safety Yellow:

Fixtures hanging from ceiling or walls that invade open space, treads of stairways, pillars, columns and posts, exposed edges of walls and platforms, handrails and guardrails, caution signs, piping that is used for hazardous, flammable, toxic, poisonous, corrosive, high temperature, or high pressure materials, striking against hazards, stumbling hazards, falling hazards, tripping hazards and "caught in between" hazards.



DuraStripe Safety Yellow

DuraStripe Safety Green


Designates area and equipment associated with First Aid.

Samples of Uses for Safety Green:

Location of first-aid kits, gas masks and stretchers, Safety bulletin boards, safety deluge showers, Safety instruction signs, piping for non-hazardous, non-poisonous, non-flammable, moderate temperature, low pressure materials such as drinking water, syrups and glycols.



DuraStripe Safety Green



ERGOMAT®



DURASTRIPE®

- OSHA Industries Color-Code



DuraStripe Safety Purple

Designates radiation hazard.

Samples of Uses for Safety Purple:

Any disposal containers designated for radioactive waste or hazardous materials and "BIOLOGICAL HAZARD" - Fluorescent orange or orange-red, or predominantly so, with lettering or symbols in a contrasting color



DuraStripe Safety Purple


DuraStripe 5S Shapes & Signs

DuraStripe 5S Shapes and Signage are perfect for any 5S or Six Sigma program, these durable floor markings will communicate safety instructions and can withstand pedestrian or forklift traffic. DuraStripe Shapes and Signage are so easy to install and reconfigure, you just peel-&-stick! This will save you time and money from having to paint floor markings.



DuraStripe 5S Shapes & Signs





WSL Warehouse Systems Limited

**FT. K, 19/F, Gold King Industrial Building,
35-41 Tai Lin Pai Road, Kwai Chung, N.T., HK**

T: +852 2328 0018 F: +852 8343 0099

E: cs@wsl.hk W: www.WSL.hk

DURASTRIPE[®]

Sole Agent (Asia Pacific Region)

~ Your One-Stop Logistics Equipment & Supplies Centre ~